

# Fuse bases

## Ceramic fuse base

Rated current  
**16, 63 A**

The fuse bases D0 are planned to be built into distribution boxes in domestic and public installations. Total security against parts under voltage is achieved by installing D0 fuse bases into domestic or industrial distribution boards. Ceramic fuse-bases are tested and certified according to IEC 60269-3-1, DIN EN 60269-1, DIN EN 60269-3 and DIN VDE 0636-301.

### Advantages

- modular construction-module 9 mm
- smaller weight and smaller height (66 mm) provide installation into the flush-mounting distribution boxes, the depth of which is 80 mm only
- by the use of gauge-piece key it is possible to change the gauge rings under voltage
- the possibility of simple substitution of base D0 1 with D0 2

### 1-pole fuse base D0

type	I <sub>n</sub> [A]	code No.	screw	with protection cover	without protection cover	click-on mounting	screw mounting	weight [g]	packaging [pcs]
D01N - K	16	002221011	E14	0		X		68	15/300
D01V - K	16	002221012	E14	0			X	66	15/300
D02N - K	63	002222011	E18	0		X		87	15/300
D02V - K	63	002222012	E18	0			X	80	15/300
D02N M5 - K	63	002222016	E18	0		X		82	15/300
D02V M5 - K	63	002222015	E18	0			X	80	15/300
D01N	16	002221001	E14		0	X		56	15/150
D01V	16	002221002	E14		0		X	59	15/150
D02N	63	002222001	E18		0	X		80	15/150
D02V	63	002222002	E18		0		X	77	15/150
D02N M5	63	002222006	E18		0	X		75	15/150
D02V M5	63	002222005	E18		0		X	72	15/150



### 1-pole fuse base D0 - U

type	I <sub>n</sub> [A]	code No.	screw	with protection cover	without protection cover	click-on mounting	screw mounting	weight [g]	packaging [pcs]
D01NU - K	16	002221111	E14	0		X		80	15/210
D01VU - K	16	002221112	E14	0			X	80	15/210
D02NU - K	63	002222111	E18	0		X		90	15/210
D02VU - K	63	002222112	E18	0			X	90	15/210





**3-pole fuse base D0**

type	I <sub>n</sub> [A]	code No.	screw	with protection cover	without protection cover	click-on mounting	screw mounting	weight [g]	packaging [pcs]
D01N/3 - K	16	002221021	E14	0		X		216	5/100
D01V/3 - K	16	002221020	E14	0			X	187	5/100
D02N/3 - K	63	002222021	E18	0		X		252	5/100
D02V/3 - K	63	002222020	E18	0			X	246	5/100
D02N/3 M5 - K	63	002222023	E18	0		X		237	5/100
D02V/3 M5 - K	63	002222022	E18	0			X	231	5/100
D01N/3	16	002221031	E14		0	X		176	5/50
D01V/3	16	002221030	E14		0		X	170	5/50
D02N/3	63	002222031	E18		0	X		235	5/50
D02V/3	63	002222030	E18		0		X	229	5/50
D02N/3 M5	63	002222033	E18		0	X		220	5/50
D02V/3 M5	63	002222032	E18		0		X	214	5/50

**Plastic fuse base**

Plastic fuse bases series PPD01 and PPD02 are mainly intended to be build into distribution boxes in domestic, office and schools installations.

Total security against parts under voltage is achieved by installing PPD0 fuse bases into domestic or industrial distribution boards. Plastic fuse bases are tested and certified according to IEC 60269-3-1, DIN EN 60269-1, DIN EN 60269-3 and DIN VDE 0636-301.

**Advantages**

- Connection at the input is possible with a clamp or with a screw, at the output it is possible to connect with a clamp
- Mounting is on a standard rail 35 mm (according to DIN EN 60715)
- Temperature resistant material
- Smaller weight of the product
- Layout is adjusted for modern build-in devices



**Fuse base PPD01**

type	I <sub>n</sub> [A]	code No.	number of poles	weight [g]	packaging [pcs]
PPD01-1	16	002221015	1	70	15
PPD01-3	16	002221022	3	220	5



**Fuse base PPD02**

type	I <sub>n</sub> [A]	code No.	number of poles	weight [g]	packaging [pcs]
PPD02-1	63	002222018	1	86	15
PPD02-3	63	002222043	3	270	5