

Manual change-over switches LAS

Generalities

Change-over switches manually operated suitable for breaking and change-over of two low voltage electrical circuits. They are made by two standard switches mechanically interlocked.

Rotary front operation by means of:

- External double insulated door-interlock handle in I and II position, IP65 degree of protection
- Direct handle standard
- Standards: IEC 60947/1-3

Manual change-over switches LAS (1-0-2)

Rated current
20-125 A

Manual change-over switches LAS 20-40A (1-0-2)

type	code No.	I_n [A]	number of poles	weight [g]	packaging [pcs]
LAS 20 3p COP	004664200	20	3	300	1
LAS 25 3p COP	004664201	25	3	300	1
LAS 32 3p COP	004664202	32	3	300	1
LAS 40 3p COP	004664203	40	3	300	1
LAS 20 4p COP	004664204	20	4	320	1
LAS 25 4p COP	004664205	25	4	320	1
LAS 32 4p COP	004664206	32	4	320	1
LAS 40 4p COP	004664207	40	4	320	1

Manual change-over switches LAS 63-125A (1-0-2)

type	code No.	I_n [A]	number of poles	weight [g]	packaging [pcs]
LAS 63 3p CO	004663105	63	3	608	1
LAS 80 3p CO	004663106	80	3	608	1
LAS 100 3p CO	004663107	100	3	608	1
LAS 125 3p CO	004663108	125	3	608	1
LAS 63 4p CO	004664105	63	4	778	1
LAS 80 4p CO	004664106	80	4	778	1
LAS 100 4p CO	004664107	100	4	778	1
LAS 125 4p CO	004664108	125	4	778	1



Accessories for manual change-over switches LAS (1-0-2)

Door interlock handle

description	code No.	for use with	weight [g]	packaging [pcs]
ROD LAS CO B, black	004664109	LAS (1-0-2) 63-125	46	1

Shaft

description	code No.	for use with	weight [g]	packaging [pcs]
SH LAS 100, 100mm	004665010	LAS (1-0-2) 63-125	8	1
SH LAS 200, 200mm	004665011	LAS (1-0-2) 63-125	14	1

4th pole

description	code No.	for use with	weight [g]	packaging [pcs]
P4 LAS 80	004665021	LAS (1-0-2) 63-125	98	1

Auxiliary contact

description	code No.	for use with	weight [g]	packaging [pcs]
PS LAS 80, 1NO+1NC, screw terminals	004665051	LAS (1-0-2) 63-125	38	1



ROD LAS CO B



SH LAS 100/200



P4 LAS 80



PS LAS 80